



## MA 263 SL



### GENERAL TECHNICAL CHARACTERISTICS

**Structure:** enamelled steel, closed firebox

**Firebox:** in Aluker®

**Fire pit:** in cast iron

**Hood:** in steel

**Opening:** door in enamelled steel with self-cleaning ceramic glass resistant up to 750 °C.  
Rise n fall door, hinged opening for cleaning

**Door profile:** in enamelled steel

**Door handle:** in enamelled steel

**Primary air:** adjustable manually

**Secondary air:** fixed

**Flue outlet:** top

**Flue damper:** manual

**Ash pan:** removable

**Fuel:** wood

**Heating:** radiant and natural convection

### TECHNICAL DATA

Room heating capacity (min-max)	m <sup>3</sup>	185 - 315
Nominal thermal efficiency	%	> 70
Rated heat output	kW	11
Consumption at rated heat output	Kg/h	4
Maximum heat output	kW	12
Maximum consumption	Kg/h	4,7
Flue outlet	Ø cm	25
Flue up to 4,5 mt	Ø cm	30
Flue over 4,5 mt	Ø cm	25
Fresh air intake (recomm. min sect.)	cm <sup>2</sup>	300
Weight	Kg	205

### ON REQUEST

- Cooking Pro kit
- Adjustable legs kit
- Positioning handles kit

Laboratory data using beech wood with less than 20% moisture content. Consumptions may vary according to the type of wood used



The availability of models may vary from Country to Country.

### Compatible Cover

ESSEN - GRAZ - AMBURGO - FRIBURGO - LIPSIA - COLONIA - COLORADO - LINZ - SALISBURGO - CALAIS - EASY - NEW ORLEANS - PORTICI - CUNEO - BORMIO

### TECHNICAL DRAWING

