

P930 M TOP STEEL

The P930 M features an aesthetic steel door to give continuity to its cladding, the Multicomfort to manage temperature with maximum comfort thanks to the remote control with thermostat, and a cast-iron firebox that ensures a long product life. With its 11 kW it is the ideal stove for heating rooms up to 110 m2. Discover all the colours and features.

P930 M TOP STEEL

A pellet stove P930 M STEEL that can manage various room temperatures also thanks to the possibility of connecting a wireless sensor for managing the Multicomfort Plus System. Features a modern square-shaped design and Steel panels with a rounded profile. Available in different colors.



GENERAL FEATURES

- Heating: Multifuoco System® with 4 power levels and manual or automatic control. Hot ductable air
- Natural Mode: yes
- Power levels: 5
- Dual Power System: 4 power levels and manual or automatic control
- Cladding / Top: steel / steel - cast iron
- Front ventilation: adjustable vent
- Humidifier: stainless steel
- Remote control with LCD display:
- Multicomfort: standard
- Multicomfort Plus: standard
- Ambient probe for temperature control: as standard feature
- Control panel with digital controls: yes
- Module WiFi - Bluetooth® for MyPiazzetta App: standard
- Wireless probe for temperature management: optional
- Timer-controlled thermostat with programming: 6 daily time frames
- Eco / Energy Saving function: yes / yes
- Glass cleaning: continuous air flow
- Cyclic brazier cleaning: yes
- Ash vacuum cleaner: as standard feature
- Installation: flush with the wall - corner
- Standard flue outlet position: top
- Optional flue outlet: top balanced flue
- One-piece firebox: airtight in steel
- Firebox: cast iron
- Door / Handle: cast iron with ceramic glass resistant up to 750°C / detachable
- Combustion air kit:
- Design door:
- Air Combustion System Function: yes
- Pellet Quality System Function: yes
- Ash conveyor: steel
- Side ventilation: optional vent, fixed
- Combustion air kit:

TECHNICAL DETAILS

- Rated thermal power (min - max) kW 4,1 - 11,0
- Efficiency (min - max) % 91,5 - 91,8
- Energy efficiency class A+ (G → A++)
- Rated consumption (min - max) kg/h 0,9 - 2,4
- Tank capacity kg 21
- Weight kg 195
- Standard flue outlet Ø mm 80
- Model P930 M TOP STEEL
- PMnom (13 % O₂) mg/Nm³ 14
- OGCnom (13 % O₂) mg/Nm³ 2

COVERS

